



BOVA



FALL ARREST





BOVA

FALL ARREST SYSTEM

Belted harness range with permanently attached shock absorbing lanyards with adjustable shoulder, leg, waist and chest straps



CODE: HARN02220



DOUBLE LEG LANYARD WITH SCAFF HOOKS

CODE: HARN02210



DOUBLE LEG LANYARD WITH SNAP HOOKS

Common features on BOVA CORE+ RANGE:

- Sizing:** • One size fits all
Standards: • SANS 50354 | SANS 50355 | SANS 50361 | SANS 50362

MATERIALS:

- Harness Webbing:** • 45mm UV-resistant polyester webbing with a minimum breaking load of 2,6 tonnes
Lanyard Webbing: • 45mm UV-resistant polyester webbing with a minimum breaking load of 2,6 tonnes
 • Lanyard length: 1 700mm
 • Lanyard length when shock absorber is fully elongated: 3 450mm
Chest Strap: • 45mm UV-resistant polyester webbing with a minimum breaking load of 2,6 tonnes
Buckles: • Interlocking, corrosion-resistant steel hooks
Hooks: • Corrosion-resistant steel hooks
 - Scaffold hooks - 50mm gate opening
 - Snap hooks - 20mm gate opening

SELECT THE CORRECT FALL ARREST SYSTEM:

- **SINGLE LEG LANYARDS:** engineered for those who are not required to navigate obstacles whilst working at heights and have no reason to detach the lanyard from the secure anchor point.
- **DOUBLE LEG LANYARDS:** engineered for those who need to navigate obstacles whilst working at heights. Through the inclusion of two legs, the wearer remains attached to at least one anchor point at all times when encountering an obstacle – one lanyard hook remains attached to the original anchor point, whilst the second hook is moved to secure a new anchor point.



BOVA

FALL ARREST

S Y S T E M

Standard harness range with permanently attached shock absorbing lanyards with adjustable leg and chest straps



CODE: HARN01220



DOUBLE LEG LANYARD WITH SCAFF HOOKS

CODE: HARN01210



DOUBLE LEG LANYARD WITH SNAP HOOKS

CODE: HARN01110



SINGLE LEG LANYARD WITH SNAP HOOK

Common features on BOVA CORE RANGE:

- Sizing:** • One size fits all
- Standards:** • SANS 50354 | SANS 50355
SANS 50361 | SANS 50362

MATERIALS:

- Harness Webbing:** • 45mm UV-resistant polyester webbing with a minimum breaking load of 2,6 tonnes
- Lanyard Webbing:** • 45mm UV-resistant polyester webbing with a minimum breaking load of 2,6 tonnes
- Lanyard length: 1 700mm
 - Lanyard length when shock absorber is fully elongated: 3 450mm
- Chest Strap:** • 45mm UV-resistant polyester webbing with a minimum breaking load of 2,6 tonnes
- Buckles:** • Interlocking, corrosion-resistant steel buckles
- Hooks:** • Corrosion-resistant steel hooks
- Scaff hooks - 50mm gate opening
 - Snap hooks - 20mm gate opening



info@bova.co.za
Proudly manufactured
in South Africa

Accredited working at heights
training and services offered by:



fallarrest@bbfsheqservices.com

Association Memberships:

